

Self-Regulating Heating Tape Freezstop Lite 85°C - FSLe



Electrical heating tape for frost protection or temperature maintenance of instrument lines and pipework in safe or hazardous locations

- Automatically adjusts heat output in response to increasing or decreasing pipe temperature
- Can be cut to length with no wastage
- Will not overheat or burnout, even when overlapped
- Approved for use in non-hazardous, hazardous and corrosive environments
- Full range of controls and accessories
- Available for 110-120VAC and 220-277 VAC

FEATURES

FREEZSTOP LITE is a light industrial/commercial grade self-regulating heating tape that can be used for freeze protection or temperature maintenance of pipework and vessels in the construction and refrigeration industries.

It can be cut-to-length at site and exact piping lengths can be matched without any complicated design considerations.

FREEZSTOP LITE is approved for use in non-hazardous, hazardous and corrosive environments to world wide standards.

Its self-regulating characteristics improve safety and reliability. FREEZSTOP LITE will not overheat or burnout, even when overlapped upon itself. Its power output is self-regulated in response to the pipe temperature.

The installation of FREEZSTOP LITE is quick and simple and requires no special skills or tools. Termination, splicing and power connection components are all provided in convenient kits.

OPTIONS

FSLe .. C Tinned copper braid providing mechanical protection or where traced equipment does not provide an effective earth path. eg. plastic pipework.

FSLe .. CT Thermoplastic overjacket over tinned copper braid provides additional protection.

FSLe .. CF Fluoropolymer overjacket over tinned copper braid provides protection where corrosive chemical solutions or vapours may be present.



SPECIFICATION

MAXIMUM TEMPERATURE 85°C (185°F)

MAX. PERMISSIBLE TEMPERATURE de-energised 85°C (185°F)

MINIMUM INSTALLATION TEMPERATURE -40°C (-40°F)
(CENELEC -20°C, -4°F)

POWER SUPPLY 110 – 120VAC, 220 – 277VAC









TEMPERATURE CLASSIFICATION up to 23W/m T6 (85°C)
31W/m and/or 277V T4 (135°C)

MAXIMUM RESISTANCE OF PROTECTIVE BRAIDING 18.2 Ohm/km

WEIGHTS AND DIMENSIONS

Type Ref	Nominal Dimensions (mm)	Weight kg/100m	Min. Bending radius	Gland Size
FSLe	8.5 x 3.9	4.6	25mm	M20
FSLe .. C	9.3 x 4.7	9.2	30mm	M20
FSLe .. CT	10.5 x 5.9	10.2	35mm	M20
FSLe .. CF	10.5 x 5.9	9.9	35mm	M20

APPROVAL DETAILS

Testing Authority	Certificate No.	Standard
CENELEC 	SCS Ex 99E3146	EN60079-0/EN60079-7
ATEX 	Sira 02ATEX3074	EN60079-0/EN60079-7 IEC62086
IEC 	Sira 02Y3064	CEI IEC62086 & IEC60079-7
FM 	3009080	ANSI/IEEE Std 515
VDE 	114665	DIN VDE 0254
CSA 	214197-1295278	C22.2 No. 130.1 C22.2 No. 130.2 C22.2 No. 138
Lloyds Register 	02/00062	EN60079-0/EN60079-7 IEEE Std515
GOST R 	POCC GB.ГБ05.В02364	GOST R 51330.0-99 (МЭК 60079-0-98) GOST R 51330.8-99

ORDERING INFORMATION

Example 12FSLe2-CT

Output 12W/m at 5°C _____

FREEZSTOP LITE _____

Supply Voltage 220 – 277VAC _____

Tinned Copper Braid _____

Thermoplastic Outerjacket _____

ACCESSORIES

Backer supply a complete range of accessories including termination/splice kits, end seals, junction boxes and controls. These items are recommended for the correct operation of FSLe products.

MAXIMUM LENGTH (m) vs. CIRCUIT BREAKER SIZE

Cat Ref	Start-up Temperature	230V			
		6A	10A	16A	20A
12FSLe	5°C	78	132	180	-
	0°C	74	124	180	-
	-20°C	56	94	150	180
	-40°C	46	76	124	154
17FSLe	5°C	62	104	146	-
	0°C	60	100	146	-
	-20°C	48	82	130	146
	-40°C	42	70	112	138
23FSLe	5°C	46	76	124	-
	0°C	42	70	114	124
	-20°C	34	56	88	110
	-40°C	28	46	72	90
31FSLe	5°C	34	58	92	102
	0°C	32	52	84	102
	-20°C	24	40	56	66
	-40°C	20	34	54	66

For use with Type C circuit breakers to BS EN60898

THERMAL RATINGS

Nominal output at 115V or 230V when FSLe is installed on insulated metal pipes.

